


## 塑料外壳金属化聚酯膜叠片式电容器(P=5.0)

## Box-type metallized polyester film capacitor(Stacked version)

## ■ 外形图 Outline Drawing



## ■ 特点

- 金属化聚酯膜, 叠片式结构
- 塑料外壳(UL94 V-0), 环氧填充
- 抗脉冲能力强

## ■ 主要用途:

- 旁路, 隔直, 耦合, 退耦
- 脉冲, 逻辑, 定时, 紧凑型节能灯
- LCD监视器整流, 汽车直流马达抑制干扰

## ■ Features

- Metallized polyester film, stacked construction
- Plastic case(UL94 V-0), Epoxy resin sealing
- High dv/dt ability

## ■ Typical Applications:

- By-passing, blocking, coupling, decoupling,
- Pulse logic, timing, compact fluorescent lamps.
- Invert for LCD monitors, automotive DC motor suppression

## ■ 技术要求 Specifications

引用标准 Reference Standard	GB/T 7332 (IEC 60384-2)		
气候类别 Climatic Category	55/125/56		
额定温度 Rated Temperature	85℃		
工作温度 Operating Temperature Range	-55℃~125℃ (+85℃ to +125℃: decreasing factor 1.25% per ℃ for U <sub>R</sub> )		
额定电压 Rated Voltage	50/63V、100V、250V、400V、500V、630V、700V		
电容量范围 Capacitance Range	0.0010μF~2.2μF		
电容量偏差 Capacitance Tolerance	± 5%(J), ± 10%(K), ± 20%(M)		
耐电压 Voltage Proof	Pattern I 型: 1.6U <sub>R</sub> (5s)、Pattern II 型: 1.4U <sub>R</sub> (5s)		
损耗角正切 Dissipation Factor	Frequency	C <sub>R</sub> < 0.1μF	C <sub>R</sub> > 0.1μF
	1kHz	< 1.0%	< 1.0%
	10kHz	< 1.5%	< 1.5%
	100kHz	< 3.0%	
绝缘电阻 Insulation Resistance	U <sub>R</sub> > 100V	> 30 000MΩ, > 10 000s, □ C <sub>R</sub> < 0.33μF C <sub>R</sub> > 0.33μF	(20℃, 100V, 1min)
	U <sub>R</sub> < 100V	> 15 000MΩ, > 5 000s, □ C <sub>R</sub> < 0.33μF C <sub>R</sub> > 0.33μF	(20℃, 10V, 1min)
最大脉冲爬升速率Maximum Pulse Rise Time (dV/dt): 若实际工作电压U比额定电压U <sub>R</sub> 低, 电容器可工作在更高的dV/dt场合。这样dV/dt允许值应为右表值乘以U <sub>R</sub> /U。 If the working voltage (U) is lower than the rated voltage (U <sub>R</sub> ), the capacitor can be worked at a higher dV/dt. In this case, the maximum allowed dV/dt is obtain by multiplying the right value with U <sub>R</sub> /U.	U <sub>R</sub> (V)	dV/dt(V/μs)	
		pattern I	pattern II
	50/63	250	75
	100	300	85
	250	400	100
	400	600	150
	500	700	200
	630	800	
	700	-	250

产品编码说明 Part number system

18 位产品代码如下(The 18 digits part number is formed as follow):

1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18
C	2	4															

第 1~3 位 型号代码(Digit 1~3 Type Code):

型号代码:C24

第 4~5 额定电压代码(Digit 4~5 Rated Voltage Code):

	A	B	C	D	E	F	G	H	J	K	L	M	N
1			16	20				50	63			1100	
2	100	125	160	200	250	315	400	500	630	800	120		
3	1000	1250	1600	2000	2500	3150	4000	5000	6300	8000	1200	1400	
	P	Q	R	S	T	U	V	W	X	Y			
1	240	300	330	440	540	600	700	850	900				
2	275	305	350	450	520		760						
3	280	310		480									

说明：参考日本 JIS 标准，字母加数位表示交流，数字加字母表示直流，例如 A2 表示 100VAC，2A 表示 100VDC

Explanation:Refer to JIS standard,Letter and then number indicate AC,but number and then Letter indicate DC,for example,2A indicate 100VDC,A2 indicate 100VAC.

第 6~8 容值代码(Digit 6~8 Capacitance Expressed in 3-digit code 3 Code):

The first 2digits indicate significant figures,and the third digit specifies the number of zero to follow.

前两位表示基数，第三个数字表示其后零的个数

This gives the capacitance in picofarads.容量值单位为皮法

For examples 举例：102=10\*10<sup>2</sup>PF=1,000PF=1.0nF=0.001uF      105=10\*10<sup>5</sup>PF=1,000,000PF=1000nF=1uF

第 9 容量偏差代码(Digit 9 Capacitance Tolerance Code):

公差 Tolerance	±5%	±10%
代码 Code	J	K

第 10~11 两个数位的脚距代码(Digit 10~11 Pitch expressed by Case two digits Code):

Mini Box Type 迷你盒装型

Pitch 脚距	2.5	5.0	7.5
Case No. 脚距代码	02	05	07

第 12 引线加工型代码(Digit 12 Lead Form Code):

Lead Type

Code 代码	L	H	K	N	M	T	S
Lead Type 引线型式	长脚	短脚	内弯青蛙脚	内弯直脚	外弯直脚	Taping	Customer Special Require

第 13~15 引线长度和偏差以 3 个数字代码表示

Digit 13~15 Lead Length(Straight) and Tolerance of Lead Length(straight): Expressed in 3-Letter Code

Example 举例：Code 代码 035:35/10=3.5mm      230:230/10=23mm

第 16~18 内部特征码

Digit 16~18 Internal use Code

## ■外形尺寸 Dimensioms(mm)

电容器厚度 (Capacitor Thickness)T	≤3.5	>3.5
外形尺寸偏差Dimension Tolerance(W,H,T)	0.2	0.4

## Pattern I (High performance)

50Vdc (30Vac)/63Vdc(40Vac)#						
CN (μF)	w	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C241J102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C241J122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C241J152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C241J182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C241J222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C241J272J05*****
0.0033	7.2	6.5	2.5	5.0	0.5	C241J332J05*****
0.0039	7.2	6.5	2.5	5.0	0.5	C241J392J05*****
0.0047	7.2	6.5	2.5	5.0	0.5	C241J472J05*****
0.0056	7.2	6.5	2.5	5.0	0.5	C241J562J05*****
0.0068	7.2	6.5	2.5	5.0	0.5	C241J682J05*****
0.0082	7.2	6.5	2.5	5.0	0.5	C241J822J05*****
0.010	7.2	6.5	2.5	5.0	0.5	C241J103J05*****
0.012	7.2	6.5	2.5	5.0	0.5	C241J123J05*****
0.015	7.2	6.5	2.5	5.0	0.5	C241J153J05*****
0.018	7.2	6.5	2.5	5.0	0.5	C241J183J05*****
0.022	7.2	6.5	2.5	5.0	0.5	C241J223J05*****
0.027	7.2	6.5	2.5	5.0	0.5	C241J273J05*****
0.033	7.2	6.5	2.5	5.0	0.5	C241J333J05*****
0.039	7.2	6.5	2.5	5.0	0.5	C241J393J05*****
0.047	7.2	6.5	2.5	5.0	0.5	C241J473J05*****
0.056	7.2	6.5	2.5	5.0	0.5	C241J563J05*****
0.068	7.2	6.5	2.5	5.0	0.5	C241J683J05*****
0.082	7.2	6.5	2.5	5.0	0.5	C241J823J05*****
0.10	7.2	6.5	2.5	5.0	0.5	C241J104J05*****
0.12	7.2	6.5	2.5	5.0	0.5	C241J124J05*****
0.15	7.2	7.5	3.5	5.0	0.5	C241J154J05*****
0.18	7.2	7.5	3.5	5.0	0.5	C241J184J05*****
0.22	7.2	7.5	3.5	5.0	0.5	C241J224J05*****
0.27	7.2	9.5	4.5	5.0	0.6	C241J274J05*****
0.33	7.2	9.5	4.5	5.0	0.6	C241J334J05*****
0.39	7.2	9.5	4.5	5.0	0.6	C241J394J05*****
0.47	7.2	10.0	5.0	5.0	0.6	C241J474J05*****
0.56	7.2	10.0	5.0	5.0	0.6	C241J564J05*****
0.68	7.2	11.0	6.0	5.0	0.6	C241J684J05*****
0.82	7.2	11.0	6.0	5.0	0.6	C241J824J05*****
1.00	7.2	11.0	6.0	5.0	0.6	C241J105J05*****

100Vdc(63Vac)						
CN (μF)	W	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C242A102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C242A122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C242A152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C242A182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C242A222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C242A272J05*****
0.0033	7.2	6.5	2.5	5.0	0.5	C242A332J05*****
0.0039	7.2	6.5	2.5	5.0	0.5	C242A392J05*****
0.0047	7.2	6.5	2.5	5.0	0.5	C242A472J05*****
0.0056	7.2	6.5	2.5	5.0	0.5	C242A562J05*****
0.0068	7.2	6.5	2.5	5.0	0.5	C242A682J05*****
0.0082	7.2	6.5	2.5	5.0	0.5	C242A822J05*****
0.010	7.2	6.5	2.5	5.0	0.5	C242A103J05*****
0.012	7.2	6.5	2.5	5.0	0.5	C242A123J05*****
0.015	7.2	6.5	2.5	5.0	0.5	C242A153J05*****
0.018	7.2	6.5	2.5	5.0	0.5	C242A183J05*****
0.022	7.2	6.5	2.5	5.0	0.5	C242A223J05*****
0.027	7.2	6.5	2.5	5.0	0.5	C242A273J05*****
0.033	7.2	6.5	2.5	5.0	0.5	C242A333J05*****
0.039	7.2	6.5	2.5	5.0	0.5	C242A393J05*****
0.047	7.2	6.5	2.5	5.0	0.5	C242A473J05*****
0.056	7.2	6.5	2.5	5.0	0.5	C242A563J05*****
0.068	7.2	6.5	2.5	5.0	0.5	C242A683J05*****
0.082	7.2	6.5	2.5	5.0	0.5	C242A823J05*****
0.10	7.2	7.5	3.5	5.0	0.5	C242A104J05*****
0.12	7.2	9.5	4.5	5.0	0.6	C242A124J05*****
0.15	7.2	9.5	4.5	5.0	0.6	C242A154J05*****
0.18	7.2	9.5	4.5	5.0	0.6	C242A184J05*****
0.22	7.2	10.0	5.0	5.0	0.6	C242A224J05*****
0.27	7.2	10.0	5.0	5.0	0.6	C242A274J05*****
0.33	7.2	11.0	6.0	5.0	0.6	C242A334J05*****
0.39	7.2	11.0	6.0	5.0	0.6	C242A394J05*****
0.47	7.2	11.0	6.0	5.0	0.6	C242A474J05*****
0.56	7.2	11.0	6.0	5.0	0.6	C242A564J05*****

250Vdc(160Vac)						
CN (μF)	W	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C242E102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C242E122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C242E152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C242E182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C242E222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C242E272J05*****
0.0033	7.2	6.5	2.5	5.0	0.5	C242E332J05*****
0.0039	7.2	6.5	2.5	5.0	0.5	C242E392J05*****
0.0047	7.2	6.5	2.5	5.0	0.5	C242E472J05*****
0.0056	7.2	6.5	2.5	5.0	0.5	C242E562J05*****
0.0068	7.2	6.5	2.5	5.0	0.5	C242E682J05*****
0.0082	7.2	6.5	2.5	5.0	0.5	C242E822J05*****
0.010	7.2	6.5	2.5	5.0	0.5	C242E103J05*****
0.012	7.2	6.5	2.5	5.0	0.5	C242E123J05*****
0.015	7.2	6.5	2.5	5.0	0.5	C242E153J05*****
0.018	7.2	6.5	2.5	5.0	0.5	C242E183J05*****
0.022	7.2	7.5	3.5	5.0	0.5	C242E223J05*****
0.027	7.2	7.5	3.5	5.0	0.5	C242E273J05*****
0.033	7.2	7.5	3.5	5.0	0.5	C242E333J05*****
0.039	7.2	7.5	3.5	5.0	0.5	C242E393J05*****
0.047	7.2	9.5	4.5	5.0	0.6	C242E473J05*****
0.056	7.2	9.5	4.5	5.0	0.6	C242E563J05*****
0.068	7.2	9.5	4.5	5.0	0.6	C242E683J05*****
0.082	7.2	10.0	5.0	5.0	0.6	C242E823J05*****
0.10	7.2	10.0	5.0	5.0	0.6	C242E104J05*****
0.12	7.2	11.0	6.0	5.0	0.6	C242E124J05*****
0.15	7.2	11.0	6.0	5.0	0.6	C242E154J05*****

备注:

1. "\*\*\*\*\*"表示内部特征代码.Internal use.
2. " #"当额定电压为50Vdc,63Vdc时,第4-5位分别是1H,1J." #"when the rated voltage is 50Vdc,63Vdc,the ding4-5 is 1H,1J.

■外形尺寸 Dimensioms(mm)

电容器厚度 ( Capacitor Thickness)T	≤3. 5	>3.5
外形尺寸偏差Dimension Tolerance(W,H,T)	0. 2	0. 4

Pattern I (High performance)

400Vdc(200Vac)						
CN (μF)	w	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C242G102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C242G122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C242G152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C242G182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C242G222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C242G272J05*****
0.0033	7.2	6.5	2.5	5.0	0.5	C242G332J05*****
0.0039	7.2	6.5	2.5	5.0	0.5	C242G392J05*****
0.0047	7.2	6.5	2.5	5.0	0.5	C242G472J05*****
0.0056	7.2	7.5	3.5	5.0	0.5	C242G562J05*****
0.0068	7.2	7.5	3.5	5.0	0.5	C242G682J05*****
0.0082	7.2	7.5	3.5	5.0	0.5	C242G822J05*****
0.010	7.2	7.5	3.5	5.0	0.5	C242G103J05*****
0.012	7.2	9.5	4.5	5.0	0.6	C242G123J05*****
0.015	7.2	9.5	4.5	5.0	0.6	C242G153J05*****
0.018	7.2	9.5	4.5	5.0	0.6	C242G183J05*****
0.022	7.2	10.0	5.0	5.0	0.6	C242G223J05*****
0.027	7.2	11.0	6.0	5.0	0.6	C242G273J05*****
0.033	7.2	11.0	6.0	5.0	0.6	C242G333J05*****
0.039	7.2	11.0	6.0	5.0	0.6	C242G393J05*****
0.047	7.2	11.0	6.0	5.0	0.6	C242G473J05*****

500Vdc(220Vac)						
CN (μF)	W	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C242H102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C242H122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C242H152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C242H182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C242H222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C242H272J05*****
0.0033	7.2	7.5	3.5	5.0	0.5	C242H332J05*****
0.0039	7.2	7.5	3.5	5.0	0.5	C242H392J05*****
0.0047	7.2	7.5	3.5	5.0	0.5	C242H472J05*****
0.0056	7.2	7.5	3.5	5.0	0.5	C242H562J05*****
0.0068	7.2	9.5	4.5	5.0	0.6	C242H682J05*****
0.0082	7.2	9.5	4.5	5.0	0.6	C242H822J05*****
0.010	7.2	9.5	4.5	5.0	0.6	C242H103J05*****
0.012	7.2	9.5	4.5	5.0	0.6	C242H123J05*****
0.015	7.2	10.0	5.0	5.0	0.6	C242H153J05*****
0.018	7.2	11.0	6.0	5.0	0.6	C242H183J05*****
0.022	7.2	11.0	6.0	5.0	0.6	C242H223J05*****
0.027	7.2	11.0	6.0	5.0	0.6	C242H273J05*****

630Vdc(220Vac)						
CN (μF)	W	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C242J102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C242J122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C242J152J05*****
0.0018	7.2	7.5	3.5	5.0	0.5	C242J182J05*****
0.0022	7.2	7.5	3.5	5.0	0.5	C242J222J05*****
0.0027	7.2	7.5	3.5	5.0	0.5	C242J272J05*****
0.0033	7.2	7.5	3.5	5.0	0.5	C242J332J05*****
0.0039	7.2	7.5	3.5	5.0	0.5	C242J392J05*****
0.0047	7.2	9.5	4.5	5.0	0.6	C242J472J05*****
0.0056	7.2	9.5	4.5	5.0	0.6	C242J562J05*****
0.0068	7.2	9.5	4.5	5.0	0.6	C242J682J05*****
0.0082	7.2	9.5	4.5	5.0	0.6	C242J822J05*****
0.010	7.2	10.0	5.0	5.0	0.6	C242J103J05*****
0.012	7.2	11.0	6.0	5.0	0.6	C242J123J05*****
0.015	7.2	11.0	6.0	5.0	0.6	C242J153J05*****
0.018	7.2	11.0	6.0	5.0	0.6	C242J183J05*****

备注:

1. "\*\*\*\*\*"表示内部特征代码.Internal use.

## ■外形尺寸 Dimensioms(mm)

电容器厚度 ( Capacitor Thickness)T	≤3.5	>3.5
外形尺寸偏差Dimension Tolerance(W,H,T)	0.2	0.4

## Pattern II (Reduced sizes)

50Vdc (30Vac)/63Vdc(40Vac)#						
CN (μF)	w	H	T	P	d	Part number
0.15	7.2	6.5	2.5	5.0	0.5	C241J154J05*****
0.18	7.2	6.5	2.5	5.0	0.5	C241J184J05*****
0.22	7.2	6.5	2.5	5.0	0.5	C241J224J05*****
0.27	7.2	6.5	2.5	5.0	0.5	C241J274J05*****
0.33	7.2	7.5	3.5	5.0	0.5	C241J334J05*****
0.39	7.2	7.5	3.5	5.0	0.5	C241J394J05*****
0.47	7.2	7.5	3.5	5.0	0.5	C241J474J05*****
0.56	7.2	9.5	4.5	5.0	0.6	C241J564J05*****
0.68	7.2	9.5	4.5	5.0	0.6	C241J684J05*****
0.82	7.2	9.5	4.5	5.0	0.6	C241J824J05*****
1.0	7.2	10.0	5.0	5.0	0.6	C241J105J05*****
1.5	7.2	5.0	6.0	5.0	0.6	C241J155J05*****
2.2	7.2	11.0	6.0	5.0	0.6	C241J225J05*****

100Vdc(63Vac)						
CN (μF)	W	H	T	P	d	Part number
0.10	7.2	6.5	2.5	5.0	0.5	C242A104J05*****
0.12	7.2	6.5	2.5	5.0	0.5	C242A124J05*****
0.15	7.2	7.5	3.5	5.0	0.5	C242A154J05*****
0.18	7.2	7.5	3.5	5.0	0.5	C242A184J05*****
0.22	7.2	7.5	3.5	5.0	0.5	C242A224J05*****
0.27	7.2	9.5	4.5	5.0	0.6	C242A274J05*****
0.33	7.2	9.5	4.5	5.0	0.6	C242A334J05*****
0.39	7.2	9.5	4.5	5.0	0.6	C242A394J05*****
0.47	7.2	10.0	5.0	5.0	0.6	C242A474J05*****
0.56	7.2	10.0	5.0	5.0	0.6	C242A564J05*****
0.68	7.2	11.0	6.0	5.0	0.6	C242A684J05*****
0.82	7.2	11.0	6.0	5.0	0.6	C242A824J05*****
1.0	7.2	11.0	6.0	5.0	0.6	C242A105J05*****

250Vdc(140Vac)						
CN (μF)	W	H	T	P	d	Part number
0.022	7.2	6.5	2.5	5.0	0.5	C242E223J05*****
0.027	7.2	6.5	2.5	5.0	0.5	C242E273J05*****
0.033	7.2	6.5	2.5	5.0	0.5	C242E333J05*****
0.039	7.2	7.5	3.5	5.0	0.5	C242E393J05*****
0.047	7.2	7.5	3.5	5.0	0.5	C242E473J05*****
0.056	7.2	7.5	3.5	5.0	0.5	C242E563J05*****
0.068	7.2	7.5	3.5	5.0	0.5	C242E683J05*****
0.082	7.2	9.5	4.5	5.0	0.6	C242E823J05*****
0.10	7.2	9.5	4.5	5.0	0.6	C242E104J05*****
0.12	7.2	9.5	4.5	5.0	0.6	C242E124J05*****
0.15	7.2	10.0	5.0	5.0	0.6	C242E154J05*****
0.18	7.2	11.0	6.0	5.0	0.6	C242E184J05*****
0.2	7.2	11.0	6.0	5.0	0.6	C242E204J05*****

400Vdc(160Vac)						
CN (μF)	w	H	T	P	d	Part number
0.0056	7.2	6.5	2.5	5.0	0.5	C242G562J05*****
0.0068	7.2	6.5	2.5	5.0	0.5	C242G682J05*****
0.0082	7.2	6.5	2.5	5.0	0.5	C242G822J05*****
0.010	7.2	6.5	2.5	5.0	0.5	C242G103J05*****
0.012	7.2	6.5	2.5	5.0	0.5	C242G123J05*****
0.015	7.2	7.5	3.5	5.0	0.5	C242G153J05*****
0.018	7.2	7.5	3.5	5.0	0.5	C242G183J05*****
0.022	7.2	7.5	3.5	5.0	0.5	C242G223J05*****
0.027	7.2	7.5	3.5	5.0	0.5	C242G273J05*****
0.033	7.2	9.5	4.5	5.0	0.6	C242G333J05*****
0.039	7.2	9.5	4.5	5.0	0.6	C242G393J05*****
0.047	7.2	9.5	4.5	5.0	0.6	C242G473J05*****
0.051	7.2	10.0	5.0	5.0	0.6	C242G513J05*****
0.056	7.2	11.0	6.0	5.0	0.6	C242G563J05*****
0.068	7.2	11.0	6.0	5.0	0.6	C242G683J05*****
0.082	7.2	11.0	6.0	5.0	0.6	C242G823J05*****
0.10	7.2	11.0	6.0	5.0	0.6	C242G104J05*****

500/630Vdc(220Vac)#						
CN (μF)	W	H	T	P	d	Part number
0.0018	7.2	6.5	2.5	5.0	0.5	C242J182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C242J222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C242J272J05*****
0.0033	7.2	6.5	2.5	5.0	0.5	C242J332J05*****
0.0039	7.2	6.5	2.5	5.0	0.5	C242J392J05*****
0.0047	7.2	6.5	2.5	5.0	0.5	C242J472J05*****
0.0056	7.2	7.5	3.5	5.0	0.5	C242J562J05*****
0.0068	7.2	7.5	3.5	5.0	0.5	C242J682J05*****
0.0082	7.2	7.5	3.5	5.0	0.5	C242J822J05*****
0.010	7.2	7.5	3.5	5.0	0.5	C242J103J05*****
0.012	7.2	9.5	4.5	5.0	0.6	C242J123J05*****
0.015	7.2	9.5	4.5	5.0	0.6	C242J153J05*****
0.018	7.2	9.5	4.5	5.0	0.6	C242J183J05*****
0.022	7.2	10.0	5.0	5.0	0.6	C242J223J05*****
0.027	7.2	11.0	6.0	5.0	0.6	C242J273J05*****
0.033	7.2	11.0	6.0	5.0	0.6	C242J333J05*****

700Vdc(250Vac)						
CN (μF)	W	H	T	P	d	Part number
0.0010	7.2	6.5	2.5	5.0	0.5	C241V102J05*****
0.0012	7.2	6.5	2.5	5.0	0.5	C241V122J05*****
0.0015	7.2	6.5	2.5	5.0	0.5	C241V152J05*****
0.0018	7.2	6.5	2.5	5.0	0.5	C241V182J05*****
0.0022	7.2	6.5	2.5	5.0	0.5	C241V222J05*****
0.0027	7.2	6.5	2.5	5.0	0.5	C241V272J05*****
0.0033	7.2	7.5	3.5	5.0	0.5	C241V332J05*****
0.0039	7.2	7.5	3.5	5.0	0.5	C241V392J05*****
0.0047	7.2	7.5	3.5	5.0	0.5	C241V472J05*****
0.0056	7.2	7.5	3.5	5.0	0.5	C241V562J05*****
0.0068	7.2	7.5	3.5	5.0	0.5	C241V682J05*****
0.0082	7.2	9.5	4.5	5.0	0.6	C241V822J05*****
0.010	7.2	9.5	4.5	5.0	0.6	C241V103J05*****
0.012	7.2	9.5	4.5	5.0	0.6	C241V123J05*****
0.015	7.2	10.0	5.0	5.0	0.6	C241V153J05*****
0.018	7.2	11.0	6.0	5.0	0.6	C241V183J05*****
0.022	7.2	11.0	6.0	5.0	0.6	C241V223J05*****

备注:

- 1."\*\*\*\*\*"表示内部特征代码.Internal use.
- 2."#"当额定电压为50Vdc,500Vdc时，第4-5位分别是1H,2H."#"when the rated voltage is 50Vdc,500Vdc,the ding4-5 is 1H,2H.